

Safety Data Sheet

Section 1 - Product Information			
Product Name: Degreaser Spotter		Supplier: Faultless Professional	
Product Code Number: 17107	Information Phone: 816-842-1230	Address: 1025 W. 8th Street Kansas City, MO 64101-1200	
Product use: Fabric and Carpet Spotter	Emergency Contact: CHEMTREC - 800-424-9300		
Section 2 - Hazard Identification			
<p>GHS Classification: Flammable liquid - Category 3; Serious Eye Damage - Category 2A; Hazardous to the Aquatic Environment - Short Term (Acute) Hazard - Category 2; Hazardous to the Aquatic Environment - Long Term (Chronic) Hazard - Category 3; Specific Target Organ Toxicity - Single Exposure (Respiratory) - Category 3</p>			
Section 2.1 - Label Elements			
Hazard Pictograms:		Precautionary Statements:	
 		<p>P210 - Keep away from heat, hot surfaces, sparks, open flame, and other ignition sources. No Smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P261 - Avoid breathing dust, fumes, gas, mist, vapors, and/or spray. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, and face protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338 - IF IN EYES: Rinse cautiously for water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists seek medical attention. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER or doctor if you feel unwell. P370+P378 - In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam to extinguish. P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents/container in accordance with local, regional, national, and/or international regulations (to be specified).</p>	
Signal Word: Warning			
Hazard Statements:			
<p>H226 - Flammable liquid and vapor. H319 - Causes serious eye irritation. H401 - Toxic to aquatic life. H412 - Harmful to aquatic life with longlasting effects. H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness.</p>			
Section 3 - Composition			
Chemical Name	CAS #	Percent w/w	
Acetone	67-64-1	45 - 55	
Poly(Oxyethylene)NonylPhenyl Ether	9016-45-9	25 - 35	
Ethoxylated Alcohols(C9-11)	68439-46-3	5 - 10	
Polyethylene glycol octyl phenyl ether	9036-19-5	5 - 9	
Iso amyl acetate	123-92-2	1 - 5	
2-Butoxyethanol	111-76-2	1 - 3	
d-Limonene	5989-27-5	1 - 3	
Section 4 - First Aid Measures			
SKIN: Wash with soap & water for 15 minutes. See physician if irritation persists			
EYES: Flush with flowing water for 15 minutes & see physician.			
INHALATION: Remove to fresh air. If breathing has stopped, apply suitable artificial respiration. Get medical help			
INGESTION: Give milk or water to dilute material; DO NOT induce vomiting. Avoid alcohol. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.			
Section 5 - Fire and Explosion Hazard Data			
Flash Point:	Limits:	Extinguishing Media:	Special Fire Fighting Procedures: Avoid exposure to fumes or vapors.
24°C	LEL: NE	Water spray, dry chemical, carbon dioxide or alcohol resistant foam if product involved.	Wear self-contained positive pressurized breathing apparatus MSHA/NIOSH Approved or equivalent to maintain TLV. UNUSUAL FIRE & EXPLOSION HAZARD: Use water spray to cool unopened containers.
	UEL: NE		

Section 6 - Accidental Release Measures

Contain and absorb spills with inert, non-combustible absorbent material (i.e. sand or vermiculite), then place in open, unsealed containers. Ensure spilled product does not enter waterways, sewers, or confined spaces. For large spills, dike area to prevent spreading.

Section 7 - Handling and Storage

Don appropriate PPE. For institutional and industrial use only, not intended for consumer use. Store upright in original closed container. Store away from heat, sparks, and open flame.

Section 8 - Exposure Controls/PPE

Ingredient	OSHA PEL:	ACGIH TLV:	PPE		General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practices. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.
Acetone	1000ppm	750ppm	Respiratory:	not normally required	
PNP Ether	NE	NE	Eye:	safety glasses/face shield	
Ethoxylated Alcohol	NE	NE	Skin:	solvent proof gloves	
PEG octyl phenyl ether	NE	NE	Ventilation:	Normal room ventilation	
2-Butoxyethanol	NE	20 ppm			

Section 9 - Physical and Chemical Properties

Appearance	Odor	Odor Threshold	pH	Melting Point	Boiling Point	Evaporation Rate	Flammability	Upper/Lower Flammability Limits	Vapor Pressure
Clear, Colorless Liquid	Solvent	NE	NA	NE	NE	< 1(water=1)	24°C	NE	17mm(Hg)
Vapor Density	Density	Specific Gravity	pH(use dil)	Solubility (H ₂ O)	Partition Coefficient	Auto Ignition Temp	Viscosity	Decomposition Temp	
.62(air = 1)	7.96	0.956	NA	emulsifies	NE	NA	thin	NE	

Section 10 - Stability and Reactivity

Product is stable. Hazardous polymerization will not occur. It is incompatible with strong oxidizing agents. If burned normal combustion products such as Carbon Dioxide, Carbon Monoxide and Nitrous Oxides may occur.

Section 11- Toxicological Information

Ingredient	Acute Toxicity (Oral LD50) Rat	Acute Toxicity (Derm. LD50)Rabbit	Skin and Eye	Carcinogen	Mutagen	Reproductive Toxicity	STOT - Single Exposure	STOT - Repeated Exposure
Acetone	5,800 mg/kg	>15800 mg/kg	irritation	NA	NA	NA	Respiratory	NA
PNP Ether	3,347 mg/kg	6,000 mg/kg	irritation	NE	NA	NE	NE	NE
Ethoxylated Alcohol	>300 mg/kg	>2,000 mg/kg	eye damage	NA	NA	NA	NA	NA
PEG octyl phenyl ether	>4,000 mg/kg	>3,000 mg/kg	irritation	NE	NA	NE	NA	NA
Iso amyl acetate	NA	NA	NA	NA	NA	NA	NA	NA
2-Butoxyethanol	1,414 mg/kg	>2,000 mg/kg	irritation	NA	NA	NA	narcotic effects	NA
d-Limonene	>2,000 mg/kg	NA	Skin Irritation	NA	NA	NA	NA	NA

Section 12 - Ecological Information

Mixture is thought to be toxic as several of the major components are toxic to the environment in moderate to large quantities.

Section 13 - Disposal Considerations

The products covered by this SDS, in their original form, are considered hazardous ignitable waste according to RCRA(40 CFR 261).Dispose of in accordance with applicable Federal, State and Local regulations.

Section 14 - Transport Information

UN number	Basic Description (DOT)	Class	Packing Group	LTD QTY
UN1993	Flammable Liquid, n.o.s.(contains acetone)	3	III	< 5L
UN number	Basic Description (IATA)	Class	Packing Group	LTD QTY
UN1993	Flammable Liquid, n.o.s.(contains acetone)	3	III	< 1L
UN number	Basic Description (IMDG)	Class	Packing Group	LTD QTY
UN1993	Flammable Liquid, n.o.s.(contains acetone)	3	III	< 5L

Section 15 - Regulatory Information

SARA Title 3 Notification: Acetone, Glycol Ethers

CERCLA: Acetone (RQ-5000lbs), Glycol Ethers (indeterminate). For more information consult 40 CFR parts 302, 355, 370, 372, and 40 CFR part 68



Warning: This product can expose you to chemicals including Acetaldehyde (CAS#75-07-0), Ethylene oxide (CAS# 75-21-8), Ethylene glycol (CAS# 107-21-1), and 1,4-dioxane (CAS# 123-91-1, which are known to the State of California to cause cancer and/or birth defects or reproductive harm. For more information go to www.P65Warnings.ca.gov

Section 16 - Other Information

WHMIS: NA

HMIS: Health - 2 Flam. - 3 R - 0 PPE- B

Date Prepared: 30 Sep 2025

Prepared by: Director of Technical Service, Research and Development

The information provided in this Safety Data Sheet is correct to the best of our knowledge and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with materials or in any process, unless specified in the text.

Legend for Abbreviations: GHS - Globally Harmonized System; CAS - Chemical Abstracts Service; NA - Not Applicable; MSHA - Mine Safety and Health Administration; NIOSH - National Institute for Occupational Safety and Health; TLV - threshold limit value; PPE - personal protection equipment; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; ACGIH - American Conference of Governmental and Industrial Hygienists; NE - Not Established; STOT - Specific Target Organ Toxicity; HMIS - Hazard Materials Identification System; NOEC - No Observed Effect Concentration; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; RQ - DOT Reportable Quantity; DOT - Department of Transportation (49 CFR parts 100 to 185); IATA - International Air Transport Association; IMDG - International Code for the maritime transport of Dangerous Goods; WHMIS - Workplace Hazardous Materials Information System (Canada).